

Repro and Print information

Information:

Telephone + fax: tel. 0032 16/56 74 63 + fax 003216/56 08 49

Email: info@rembrandt.be

Web: www.rembrandt.be

Print process: offset sheetfed

Material: Carton

To plates: CTP

Files to deliver:

Pdf (High Resolution)

If Pdf is not possible:

Adobe Illustrator ("create pdf Compatible File" marked and text vectorised)

Technical printing information:

Screen ruling	85-200lpi
Maximum total inkcoverage	280%
Screen angles	C15 M75 Y90 K45
Dot shape	elliptic
Minimal printable dot	2%
Maximal printable dot	98%
Minimal text weight	4pt
Minimal reverse text weight	6pt
Minimal line thickness	0,17mm
Size barcode	80% - 200%
BWR value barcode	0 mm
Maximum numbers of colors	6

Technical Specifications:

Diecut	put diecut in a PMS color and in overprint
Text	vectorised (also deliver used fonts)
Optimal resolution	color and/or grayscale images 300dpi
Date position	put on diecut
Cut-out in box	leave the image in the cut-out
Bleed	5mm
Trapping	standard 0,07mm/ we also make the trapping
Colors	remove all not used colors
RGB images	not allowed

To deliver:

- Digital files according to above technical specifications
- (color) print

If you have any problems creating the correct file please contact us so we can help you making it.
Because information can be lost because of conversion it is always necessary to check our 'pdf for approval' very carefully on layout and text.

We thank you for your cooperation.